



## DIGITAL INSTANT HOT WATER DISPENSER

No More Waiting for Hot Water!



### KEY FEATURES SUMMARY

- Digital Soft-Touch Control Panel
- On/Off Button with Vacation-Mode
- Seven Pre-Set Temperatures = 167°-208°F
- Temperature Settings = 3° increments
- Digital Temperature Control Within 1-2°
- Patent Pending Engineering
- Built-In Dry Burn and Overheat Sensors
- Built-In 60 psi PRV w/Patented Baffle Fill System
- 304 Stainless Steel Tank 0.6 USG (2.4 litres)
- Encased Element Prevents Limescale Build-Up
- Double Venturi Reduces Faucet "Dripping/Spitting"
- 60-Cups Per Hour Capacity
- Cold Start Up 8-10 minutes
- Reheat After Use 4-5-minutes
- PSU 5V
- Standby Power 1W
- 1500-Watt/120-Volt Rapid-Recovery Element
- Standby Reheat @ 6° Temperature-Drop
- Quality Metal Housing with 4 Base Mounted Feet
- Cabinet-Side or Floor-Mount Install Options
- Space-Saving 7.5" W x 7.5" D x 10.75" H
- Compatible with RO Filtration Systems
- Compatible with all BTI Aqua-Solutions Faucets
- 4-Pack Master Carton
- UL Certified
- USA/Canada Electrical Approvals
- 5-Year Warranty

[www.btiaquasolutions.com](http://www.btiaquasolutions.com)

7022 S. Revere Parkway Suite 240 • Centennial, CO 80112 • 720.322.0800 (o) 720.322.0801 (f)



## POINT-OF-USE FILTRATION SYSTEM



### KEY FEATURES SUMMARY

**Eco-Friendly • Recyclable**  
**Reduces Carbon-Footprint up to 90% vs. Traditional Filters' Capacity**  
**Average Family Of 4 Uses 1200-1500 Gallons Annually**  
**Cartridge Capacity is 1500 US Gallons/5,678 Liters**  
**Minimum Flow-Rate is .55 US Gallons/2.1 Liters**  
**Cartridge Needs Replacement Once Per Year**

### CERTIFICATIONS

**System Certified at .5-Micron with Carbon-Block Filter**  
**NSF/ANSI Standard 53 - Reduction of Asbestos, Cyst, Lead**  
**NSF/ANSI Standard 42 - Reduction of Chlorine, Odor, Scale**  
**Additional Internal Wrap Material - Silt Reduction to Ensure Optimal Performance**

### SPECIFICATIONS

**Space-Saving Design • 3" Diameter x 11.5" High**  
**Cabinet-Side Mounting**  
**Built-In Pressure Reducing Valve (PRV)**  
**Auto Shut-Off Head for Ease when Replacing Cartridge**  
**Complete Easy-Install System Includes:**  
**Mounting Bracket, Mounting Screws, Chloramine/UV Resistant Tubing,**  
**Installed 90° Stem Elbow, John Guest Angle Shut-Off Valve, Teflon Tape**

[www.btiaquasolutions.com](http://www.btiaquasolutions.com)

7022 S. Revere Parkway Suite 240 • Centennial, CO 80112 • 720.322.0800 (o) 720.322.0801 (f)



ITEM FLC1000  
ITEM FLC1000-2

## POINT-OF-USE FILTRATION SYSTEM



ITEM FLC1000  
SINGLE  
REPLACEMENT CARTRIDGE



ITEM FLC1000-2  
2-PACK  
REPLACEMENT CARTRIDGE

[www.btiaquasolutions.com](http://www.btiaquasolutions.com)

7022 S. Revere Parkway Suite 240 • Centennial, CO 80112 • 720.322.0800 (o) 720.322.0801 (f)